

**TERRAIN****URBAN**

rollerbug

c://drive

CARSEAT CLIP INSTRUCTIONS

IMPORTANT, KEEP FOR FUTURE REFERENCE

These instructions are for the Carseat Clips which fit the following model strollers:

Terrain Single - T1204-000

Urban Single - U1204-000

Rollerbug Single - R1204-000

C:drive Single - C1204-000




⚠ WARNING


- Do not use this Carseat Clip until you have read and understood the instructions!
- Never leave your child unattended.
- This Carseat Clip fits most infant car seats. Check car seat compatibility with Authorized Dealer or Distributor.
- Do not use accessories not designed for your stroller as they may be unsafe.

The Sunhood and Seat need to be removed from stroller before fitting Carseat Clip. Store items removed in a dry safe place.

Removing Sunhood




1 Standing beside stroller and using a degree of force, pull sunhood support wire towards you by about 50mm/2in.



2 Remove support wire 1 from plastic joint 2 on the side nearest to you. Then remove wire from the plastic joint on the other side.


3 Unfasten sunhood fabric from stroller frame and seat near the handle bar.

Removing Seat



1 Unfasten seat from frame along side tubes.

2 Unfasten strap underneath seat at point A (does not apply to Terrain models).




3 Push seat forward, then slide fabric off seat support wire.


4 Remove seat support wire from stroller frame at B and C.

There are three different Carseat Clips. Check the label on the Carseat Clip to ensure you have the correct one for your model stroller. The same clip fits the Rollerbug and C:drive frame.

Fitting Carseat Clip to Frame of Stroller




1 Fit fasteners which attach fabric part of Carseat Clip to Frame on both sides, ensuring fabric passes over and around frame tubes (total of 4 fasteners).




2 Fit Carseat Clip bracket by pulling claws out and fitting them over second fastener, 130mm/5in up from the heel rest on stroller frame.

3 Buckle safety strap between claws on bracket.


Fitting Car Seat onto Carseat Clip



1 Place car seat in Carseat Clip so that when child is in car seat they will face the stroller handle bar. Make sure car seat fits snugly into the rear part of Carseat Clip.



2 Pass wide straps on each side of Carseat Clip upward and through slots provided on each side of car seat. (The slots are the same openings as used for car seat belt.)



3 Buckle wide strap across top of car seat and tighten firmly by pulling on free end of strap.

⚠ WARNING! Check car seat and Carseat Clip are firmly and securely fastened. Make sure baby is harnessed into the car seat using the car seat manufacturer's instructions.